



COST-EFFECTIVE FACE MASKS

MOQ: 2000 units

While Stocks Last | Unbranded
Lead time: 1 week

TECHNICAL DATA

70 g/m² Black Spunbond Non-Woven Fabric

Description: 70 g/m² is an extruded Polypropylene fabric intended for conversion into multi-purpose use. The fabric is suitable for Ultra-Sonic welding constructed of 100% (virgin PP).

Property	Unit	Value	Tolerance
Reel Width	Millimetres	2100	2095-2105
Core Inner Diameter	Millimetres	76	N/A
Roll Length	Metres	250	200-300
Fabric GSM	Grams/square meter	70	69-71

KEY PERFORMANCE AREAS

Overall appearance	Free of excessive slack and baggy edges
Colour	Black as per agreed standard
Packing	Rolls to be shrouded in clear plastic with ID label
Transportation & Storage	Transported & stored in horizontal position
Overall condition on receipt	Dry and Dust Free
Storage conditions	Store in a cool dry area away from direct sunlight. Sunlight will result in the product discolouration

PAYMENT TERMS

Full payment upfront on confirmation of order.

For more information and pricing please contact:
IGNITION MARKETING
info@ignitionmarketing.co.za | 010 593 6400
www.ignitionmarketing.co.za